PHOENIX Instrument
Lab Solutions

BTA-Series

The BTA-Series is equipped with the revolutionary UNIBLOC-weighing system. It guarantees brilliant stability, response and reliability characteristics. The innovative and compact construction of the weighing cell in relation with the digital process technology enables fastest weighing results and highest stability.

BTA-Series

5 Years Warranty

- automatic adjustment to environmental conditions
- easy handling of all procedures
- RS-232 interface
- weighing in different units
- weighing below the balance
- direct data transfer into Windows application by Windows direct function
- various application programs (e. g. formulation, counting, animal weighing...)
- GLP/GMP-conform protocol
- user-defined printing intervals
- aluminum die-cast housing
- protection cover as standard
- backlit display





BTA-6202

Three calibration procedures

- fully automatic calibration after temperature deviation
- fully automatic calibration at user-defined time intervals
- calibration per push CAL-button with built-in calibration weight

Model	Accuracy	Capacity	Pan Size	Meas. Time
BTA-1023	0.001 g	1,020 g	108 x 105 mm	3 sec
BTA-623	0.001 g	620 g	108 x 105 mm	3 sec
BTA-423	0.001 g	420 g	108 x 105 mm	3 sec
BTA-6202	0.01 g	6,200 g	170 x 180 mm	3 sec
BTA-4202	0.01 g	4,200 g	170 x 180 mm	3 sec
BTA-2202	0.01 g	2,200 g	170 x 180 mm	3 sec
BTA-822	0.01 g	820 g	108 x 105 mm	3 sec
BTA-8201	0.1 g	8,200 g	170 x 180 mm	3 sec
BTA-4201	0.1 g	4,200 g	170 x 180 mm	3 sec

info@phoenix-instrument.de • Tel. +49 (5131) 90818 -30
Heinkelstr. 4 • D-30827 Garbsen • www.phoenix-instrument.de