PHOENIX Instrument
Lab Solutions

Centrifuge CD-0412-50

Whether in environmental, biological or analytical laboratories - in all areas of the laboratory world there is a need to centrifuge samples up to 50 ml quickly and cost-effectively.

With the CD-0412-50, Phoenix Instrument offers exactly the right centrifuge for these requirements. The rotor has 6 holes for 15 ml tubes and 6 holes for 50 ml tubes. This means that it can be universally equipped with either 15 ml plastic tubes or 50 ml plastic tubes.



CD-0412-50

CD-0412-50

- Fix angle rotor (54°) for 6 x 50 ml or 6 x 15 ml
- Automatic self-diagnosis to control all functions
- backlit LCD-display for easy-read out of parameter such as Speed, RCF and time
- easy, intuitive operation
- Timer function 0.5 - 99 minutes
- Timer starts after the selected speed is reached
- Quick spin function
- Lid with electric lock and automatic release function to save processing time and prevent sample overheating
- Maintenance free brushless motor

2 Years Warranty

Technical Data	CD-0412-50
Speed	300 - 4,000 rpm
Increment	100 rpm steps
Max. RCF	1,800 g
Timer	0.5 - 99 minutes, continous
Noise	<54 dB (A)
Dimensions	29 x 36 x 20 cm
Weight	6 kg
Capacity	6 x 15 ml or 6 x 50 ml
Rotor	54° fix angle
Voltage • Frequency	100 - 240 V • 50/60 Hz
Power	70 W
Shipping includes	CD-A6-50P

Accesories

CD-A6-50P	Rotor 6 x 15 ml or 6 x 50 ml
CD04-R50P	Plastic tubes with round bottom, 50 ml

info@phoenix-instrument.de • Tel. +49 (5131) 90818 -30
Heinkelstr. 4 • D-30827 Garbsen • www.phoenix-instrument.de