PHOENIX Instrument
Lab Solutions

Centrifuge CD-0424

The new multi-purpose centrifuge CD-0424 is versatile and can be used in applications from clinical to biochemical for qualitative analysis of serum, plasma, blood, and urine.



CD-0424

CD-0424

- Maximum up to 4000rpm Speed can be set in RPM/RCF, with 3 customizable routines programs (Blood, Urine & Fecal)
- 3 acceleration level & 4 level deceleration
- Maximum capacity 50 mL x 4, Suitable for different sizes of blood collection tubes and centrifuge tubes for both, swing-out and fix angle rotor
- Quiet, compact, and convenient with Easy-to-read LCD display
- Automatic internal diagnosis and self-detection
- Maintenance-free brushless DC motor.

2 Years Warranty

Accesories

CD-S6-15	Swing rotor for CD-0424, 6 x 15 ml, max. 4,000 rpm
CD-S4-50	Swing rotor for CD-0424, 4 x 50 ml, max. 4,000 rpm
CD-24-15P	Fix angle rotor for CD-0424, 24 x 15 ml, max. 4,000 rpm
CD-A8-15P	Fix angle rotor for CD-0424, 8 x 15 ml, max. 4,000 rpm
CD-15-P30	Adapter 50 ml to 15 ml, for Tubes 17 x 120 mm and 13/16 x 100 mm Tubes, 4 pcs.
CD-15-P22	Adapter 15 ml to 13/16 x 100 mm, 24 pcs.
CD-A5-P17	Adapter 15 ml to 5 ml, 13 x 75 mm, 24 pcs.
CD-A2-P17	Adapter to 2 ml, 24 pcs.

Technical Data	CD-0424
Speed	500 - 4,000 rpm
Increment	100 rpm steps
Max. RCF	2,500 g
Timer	1 - 99 minutes, continous
Noise	< 62 dB (A)
Dimension (DxWxH)	37 x 44 x 27 cm
Weight	14.5 kg
Max. Capacity	4 x 50 ml
Rotor	Fix angle or swing rotor
Safety	Door interlock, overspeed detector, automatic internal diagnosis
Voltage • Frequency	100 - 240 V • 50/60 Hz
Power	70 W
Shipping includes	4 x 50 ml swing rotor and adapter

info@phoenix-instrument.de • Tel. +49 (5131) 90818 -30
Heinkelstr. 4 • D-30827 Garbsen • www.phoenix-instrument.de