PHOENIX Instrument
Lab Solutions

Low Speed Centrifuge CD-0506

The new centrifuge CD-0506, supplied with a built in fixed angle rotor which can hold up to 6 tubes each 15 ml / 10 ml / 7 ml / 5 ml / 1.5/2 ml. It is widely used for blood or urine separation in medical routine practice in hospitals, clinics or research institutes.

CD-0506

- Speed range from 300 - 5,000 rpm
- Rotor speed can be set and displayed by rpm or G-force
- Defined program by knob will be stored and activated when power on
- Two programs P1/P2, easy to start the procedure by one key
- Two deceleration speeds setting to meet different requirements
- Easy-to-read processing display and sound alert
- Automatic lid-lock release after running
- Maintenance-free brushless DC motor
- Rotor and Adapter included

2 Years Warranty



CD-0506



Technical Data	CD-0506
Speed	300 - 5,000 rpm
Increment	10 rpm
Max. RCF	2,600 g
Timer	0.5-99 minutes, continous
Noise	< 54 dB (A)
Dimension (DxWxH)	24 x 30 x 18 cm
Weight	5.2 kg
Max. Capacity	6 x 15 ml
Rotor	54° fix angle
Safety	Door interlock, overspeed detector, automatic internal diagnosis
Voltage • Frequency	100 - 240 V • 50/60 Hz
Power	70 W
Shipping includes	Rotor and adapter

Accesories

CD05-6-15	Rotor, 6 x 15 ml for CD-0506
CD05-4-50	Rotor, 4 x 50 ml for CD-0506
CD05-A2	Adapter for 1.5/2 ml, 6 pcs
CD05-A5	Adapter for 3/5 ml, 6 pcs



Adapter
CD05-A2 and CD05-A

info@phoenix-instrument.de • Tel. +49 (5131) 90818 -30
Heinkelstr. 4 • D-30827 Garbsen • www.phoenix-instrument.de