PHOENIX Instrument
Lab Solutions

Hematocrit Centrifuge CH-1424

Hematocrit centrifuge with CH-24-HR rotor is used for determination of volume fractions of erythrocytes in blood and also for separation of micro blood and solution.

Hematocrit centrifuge with CH24-24-2 rotor is used for extraction of DNA and RNA.



CH-1424

CH-1424

- Speed range of 200-14,000 rpm, max. RCF 18,260 g
- Two rotors, hematocrit rotor with max. capacity 24 capillary tubes and 2 ml × 24 rotor
- Precise control speed and time with efficient separation
- Self diagnostic, control of speed and temperature
- User-friendly large LCD display shows running information
- Both RPM or G-force can be set and displayed

2 Years Warranty

Accesories

CH24-HR	Hematocrit rotor with lid and reading disk, 24 x capillary tubes
CH24-24-2	Rotor with lid, 24 x 1,5/2 ml
CD12-A02	Adapter, 2 ml to 0,2 ml, 24 Pcs
CD12-A05	Adapter, 2 ml to 0,5 ml, 24 Pcs

Technical Data	CH-1424
Speed	200 - 12,000 rpm
Increment	10 rpm steps
Max. RCF	18,260 g
Timer	0.5 - 99 minutes, continous
Noise	< 60 dB (A)
Dimension (DxWxH)	28 x 36 x 26 cm
Weight	10 kg (without rotor)
Max. Capacity	24 x capillary, 24 x 1.5/2 ml
Rotor	Hematocrit rotor: 24 x capillary
Voltage • Frequency	100 - 240 V • 50/60 Hz
Power	160 W
Shipping includes	CH24-H

info@phoenix-instrument.de • Tel. +49 (5131) 90818 -30
Heinkelstr. 4 • D-30827 Garbsen • www.phoenix-instrument.de