PHOENIX Instrument
Lab Solutions

Rocking Shaker RS-RS 6 and 3D-Shaker RS-DS 6

Newly developed compact shaker, designed for time-dependent and low speed-sensitive shaking applications such as ELISA washes, enzyme immunoassays, protein synthesis, hybridization staining/destaining gels, immune precipitation and Western blots, cell culture, pharmaceutical profiling, etc.



2 years warranty

RS-DS 6

RS-RS 6 and RS-DS 6

- Double LED`s for separate display of speed and time
- compact shaker with a max. capacity of 2 kg
- Continuous or timer operation mode
- Fixed work plate
- Maintenance-free, brushless DC motor
- Easy operation

Technical Data	RS-RS 6	RS-DS 6
Voltage	100 - 240 V	
Power	20 W	
Shaking movement	Sea-Saw	3D-Motion
Shaking Angle	7 °	10 °
Max. shaking weight	2 kg	
Speed	10 - 80 rpm	
Timer	1 min - 19 h 59 min	
Adjustment Speed / Time	Digital	
Dimension	295 x 350 x 125 mm	295 x 350 x 170 mm
Platform size	268 x 268 mm	
Protection class	IP 21	
Weight	3.1 kg	3.7 kg



RS-RS 6

info@phoenix-instrument.de • Tel. +49 (5131) 90818 -30
Heinkelstr. 4 • D-30827 Garbsen • www.phoenix-instrument.de